

1/2 Section for 1/2 Well
Against Property Line
(Special Condition)

Curb

Tree

Porous Concrete
Treewell Cover
Install 1/2 Sections
Parallel with Curb

PLAN

Treated Douglas Fir
Stake Only

Minimum Size
25 Gallon Container

Note:
Direction of Main Branching
Shall Be Parallel to
Planting Strip and Not
into Roadway

DIRECTION OF WIND

Expanding Tree
Trunk Guard

2"x2"x8'-0" Treated
Douglas Fir Stake
Only. Do Not Stake
Thru Rootball

Porous Concrete Treewell Cover
Cover 3" Thick-2200 lbs. psi
Popcorn Texture Water Flushed
Before Dry for Porosity Casted
Off-Site

Rubber or Plastic
Fabric Ties. Do Not Use
Wire. Nail to Stake
Do Not Choke Tree

Concrete Curb

Sidewalk

4" Deep 1/2"Ø Cinders

Approved Root
Control Barrier
Min. 19" Depth

Rootball

10 "Agriform"
(20-10-5) Tablets
Evenly Around
Rootball 6" Below
Top of Rootball

Backfill Mixture:
1-Part Approved
Organic Matter
4-Parts Exist. Topsoil

Tamped Backfill

19" min. or unless
designated otherwise
on the Plan

Loosen Additional 6" at Bottom
of Pit. 2 lbs. of "Ferto"
(6-4-2) or Gro Power
(5-3-1) Humus

Note:

1. Scarify All Sides of Planting Pit
2. Remove All Stakes and Guy Wires
When Tree is Well Established and
Supports Are No Longer Needed

ELEVATION

L-3(F)

CITY COUNTY OF HONOLULU

**STREET TREE PLANTING
DETAIL (WITH COVER)**

STANDARD
DETAILS

L-3

SCALE: NOT TO SCALE

REVISED: APRIL 2003